

TCS Preliminary Design Review Part 2

Section 6 Route & Payload Planner CSCI

3-4 February 1998 Bill Aumack




- Top Level CSC Design
- TCS Data Server & UIM Integration
- TCS Route & Payload Planner Sizing
- TCS Route & Payload Planner Data Overview
- TCS Route & Payload Planner Directory Structure




Top Level CSC Design








S/W Architecture – Graphics







S/W Architecture – Autorouter














TCS Data Server & UIM Integration



TCS Data Server & UIM Integration


Integrated for Data Exchange, Integrated to JMTK Chart





TCS Data Server & UIM Integration (con't)

Integrate Data Manager and UIM





- Data Manager Functions will be merged into the TCS RPP
- Data will be migrated from static sources to DII sources
 - Threat data will be DII in Block 0
- The user interface will be changed from calls to X & Motif to calls to the UIM



TCS Route & Payload Planner Sizing




- Total disk size as delivered (including all subdirectories)
 - ~ 338 Megs
 - This can grow as more missions and data is stored.
- Executables disk size
 - GUI is ~ 4.5 Megs
 - Router is ~ 10 Megs
 - Three small report programs about 1 Meg each
- Executables memory size
 - Gui is variable ~ 40 Megs (depends on what is loaded)
 - Router is ~ 67 Megs



TCS Route & Payload Planner Data Overview





Databases



TCS Route & Payload Planner Directory Structure



- Base directory is \$TCS_HOME/TCSRPP
- Sub-Directories include
 - control
 - fpdb
 - thdb
 - tieup
 - wind
 - template
 - missions
 - segments
 - mask
 - compdted

18



control

- One control database per aircraft variant
 - Each is a sub-directory of the control database
- Contains Air Vehicle parameters
 - Flight Performance tables
- Will require about 1+ Megs of storage per aircraft variant



Sub-Directory Contents (con't)

- fpdb
 - One Footprint Database per aircraft type
 - Each is a sub-directory of the control database
 - predator and outrider are the currently defined aircraft types
 - Contains RCS related information
 - RCS data used by the router
 - Footprint data files displayed by the GUI
 - Storage requirements vary widely with number of footprints generated and complexity of footprints resulting from the RCS data



- thdb
 - Threat Database
 - Software is capable of supporting multiple threat databases
 - Block 0 will get threat data from DII
 - Can require 5+ Megs of storage for 50,000 threat sites



- tieup
 - Contains planning elements
 - Contains Airbases
 - Contains Targets
 - Contains GDTs
 - Requires about 2 Megs of storage



wind

- Winds database
- Software can also support forecast winds file of the same format
- Requires about 12 Megs of storage

template

- Used internally by the mission planner
- Requires about 190 K of storage



missions

- Central location for all mission storage
- These are the complete missions stored in ASCII text formatted files
- Storage requirements vary with size of missions

• segments

- Central location for storage of all mission segments
- Segments are imported/exported into missions
- Storage requirements vary with size of segments



- mask
 - Terrain Mask database
 - Masks are stored by location in a directory structure which parallels the Level 1 DTED directories
 - Each mask requires about 472 K of storage
- compdted
 - Compressed DTED database
 - The directory structure parallels the Level 1 DTED directories
 - Requires about 260 Megs of storage